



Model shown is TS 43

Main Data	TS 43	TS 4 VP
Capacity, kg/lbs	6 (13.2)	4 (8.8)
Hanging length, m (ft)	16 (52.5)	16 (52.5)
Heating effect, kW	1.5	-
Part no	131043	131040
Consumption data, normal temperature		
Drying time, min	85	90
DRying Capacity, g/min	25	22

*Drying of 4 kg cotton (dry weight) washed and high-spinned.

TS 43 / TS 4 VP

Compact Drying Cabinets

TS 43 and TS 4 VP are excellent drying cabinets, perfect for rooms where space is limited. The cabinets are 60 cm (23.4 inches) wide. TS 43 E holds 6 kg (13.2 lbs) of laundry and TS 4 VP holds 4 kg (8.8 lbs) of laundry. They are equipped with an extendible hanging system which simplifies the laundry operation.

Drying cabinets are great complements to tumble dryers since they dry without any mechanical action. In TS 43 all controls and electrical components are placed in a pull-out fan package which makes it easy to repair and maintain. TS 4 VP uses heat pump technology for an even more efficient and gentle drying.

Details

- Capacity 6 kg (13.2 lbs) resp. 4 kg (8.8 lbs)
- Hanging length 16 m (52,5 ft)
- Energy consumption 2,5 resp. 1,2 kWh
- Compact design
- Control panel with LCD
- Two humidity controlled automatic programs
- Timed drying - TS 43
- Extendible hanging system
- The door can be ordered right or left hanging - TS 43
- Overheat protection
- Baskets as optional extra
- Hook rack as optional extra
- Touch buttons - TS 4 VP
- 5 selectable languages - TS 4 VP

About PODAB


PODAB is a Swedish company that has been in the laundry business since 1945. They develop, manufacture and market quality products at competitive prices for multiple apartment buildings, laundry rooms and for professional use.

Contact us


If you have any questions, please feel free to contact us on 07515 683134 . You can also visit our website at www.drypod.ie

Drying Cabinet		TS 43	TS 4 VP
Electrical connections	Phase/Voltage/Frequency	1~N/230V/50-60Hz	1~N/230V/50-60Hz
	Total effect, kW	2.04	0.9
	Fuse, A	10	10
	Cable length, mm (inch)	2400 (94.5)	2500 (98.4)
Air connections	Outlet exhaust, Ø mm (inch)	100 (3.93)	-
	Outlet air flow, m³/h (ft³/h)	95 (3355)	-
Heat pump	Condensate pipe, Ø mm (inch)	-	13 (1/2)
	Refrigerant	-	R407C
	Amount of refrigerant, g (oz)	-	300 (10.6)
Optional extras	Air exchanger 1 vent., part no	141009	-
	Air exchanger 2 vent., part no	141018	-
Sound level	Airborne sound level, dB(A)	55	52
Weight	Net, kg (lbs)	60 (132)	95 (209)
	Shipping data net, kg (lbs)	65 (143)	100 (220)


Front



Left Side



Rear Side



Model shown is TS 43

Dimensions, mm (inch)	A	B	C	D
	Width	Depth	Height	Exhaust position from back
TS 43 E	595 (23.4)	641 (25.2)	1939 (76.3)	100 (3.9)
TS 43 VP	595 (23.4)	675 (26.6)	1925 (75.8)	-

